

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Addiese: COMMISSIONER FOR PATENTS P O Box 1450 Alexandra, Virginia 22313-1450 www.wepto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/588,327	12/12/2006	Georg Zepf	30071/42016	5710
4743 MARSHALL.	7590 03/03/200 GERSTEIN & BORUN	EXAM	EXAMINER	
233 SOUTH WACKER DRIVE			CUMBESS, YOLANDA R	
6300 SEARS T CHICAGO, II		ART UNIT	PAPER NUMBER	
			3651	
			MAIL DATE	DELIVERY MODE
			03/03/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.	Applicant(s)				
10/588,327	ZEPF, GEORG				
Examiner	Art Unit				
YOLANDA CUMBESS	3651				

The MAILING DATE of this communication appears on the cover sheet with the correspondence address

Period for Reply	ne cover sneet with the correspondence address				
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET WHICHEVER IS LONGER, FROM THE MALING DATE OF Edensions of time may be available under the provisions of 37 CFR 1.136(a). In or after SIX (b) MONTH'S from the missible under the provisions of 37 CFR 1.136(a). In or after SIX (b) MONTH'S from the missible of the communication. Failure to reply within the set or extended period for reply will by statistic, cause the a Any reply received by the Officio later than three months after the mailing date of this earmed pattern term adjustment. See 37 CFR 1.74(b).	THIS COMMUNICATION. event, however, may a reply be timely filed I will expire SIX (6) MONTHS from the mailing date of this communication, pplication to become ABANDONED (35 U.S.C. § 133).				
Status					
1) Responsive to communication(s) filed on 03 August 200	<u>06</u> .				
2a) This action is FINAL . 2b) This action is	non-final.				
3) Since this application is in condition for allowance exce	pt for formal matters, prosecution as to the merits is				
closed in accordance with the practice under Ex parte C	Quayle, 1935 C.D. 11, 453 O.G. 213.				
Disposition of Claims					
4) Claim(s) 1-23 is/are pending in the application.					
4a) Of the above claim(s) is/are withdrawn from o	consideration.				
5) Claim(s) is/are allowed.					
6)⊠ Claim(s) <u>1-23</u> is/are rejected.					
7)⊠ Claim(s) 1 is/are objected to.					
8) Claim(s) are subject to restriction and/or election	requirement.				
Application Papers					
9) The specification is objected to by the Examiner.					
10)⊠ The drawing(s) filed on <u>03 August 2006</u> is/are: a)⊠ acc	cepted or b) objected to by the Examiner.				
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).				
Replacement drawing sheet(s) including the correction is requ 11) The oath or declaration is objected to by the Examiner. I					
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreign priority u	inder 35 U.S.C. § 119(a)-(d) or (f).				
a) All b) Some * c) None of:					
1. Certified copies of the priority documents have be	een received.				
Certified copies of the priority documents have be	een received in Application No				
Copies of the certified copies of the priority docur	ments have been received in this National Stage				
application from the International Bureau (PCT R	ule 17.2(a)).				
* See the attached detailed Office action for a list of the ce	rtified copies not received.				
Attachment(s)					
1) Notice of References Cited (PTO-892)	Interview Summary (PTO-413) Paper No(s)/Mail Date				
Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO/95/08)	5) Notice of Informal Patent Application				
Paper No(s)/Mail Date 8/3/2006.	6) Other:				

U.S.	Patent a	nd Trade	smark Offic
PT	OL-326	(Rev	(80-80

Page 2

Application/Control Number: 10/588,327

Art Unit: 3651

DETAILED ACTION

Claim Objections

Claim 1 is objected to because of the following informalities: Where a claim sets forth a plurality of elements or steps, each element of step of the claim should be separated by a line indentation. See, MPEP 608.01(m); 37 CFR 1.75(i). Appropriate correction is required.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claims 1-23 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

The claims are generally narrative and indefinite, failing to conform with current U.S. practice. They appear to be a literal translation into English from a foreign document and are replete with grammatical and idiomatic errors.

Claim 16 recites "the container handling component comprises are of a closing device, inspection device, and labeling machine". It is unclear as to whether the container handling component comprises one of the closing device, inspection device, or a labeling machine, or all three. Appropriate clarification is needed.

Art Unit: 3651

Claim Rejections - 35 USC § 102; 35 USC § 103

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior at are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1, 5-10, 15, 18, and 22 are rejected under 35 U.S.C. 102(b) as anticipated by or, in the alternative, under 35 U.S.C. 103(a) as obvious over Stocchi (US Pg. Pub 2003/0075547). Relative to claims 1, 5-10, 15, 18, and 22, Stocchi discloses an apparatus support structure (10) (Fig. 1) for container handling machines, comprising: entry and exit stars (14)(Fig. 1) that are arranged on a support housing (26)(Fig. 1) and which are drivable from the inside of the support housing (26), with a star configuration (Fig. 1-2)(Page 2, Para. 0037, lines 1-5) that is defined by the relative positioning of the entry and exit stars (14), wherein the support housing (26)(Fig. 1) is within the star configuration and fixed above the floor plane (Fig. 1) and beneath the transport plane (Fig. 1) in a support structure (10) which stands on the floor (Fig. 1), wherein the support structure (10) is substantially horizontal and defines the fixation plane (Fig. 1), wherein the support structure (10) is formed of the sections (see sections

Art Unit: 3651

near Ref. 10, between Ref. 12) and floor feet (12) are connected to each other at nodes (see connection point of Ref. 12 and 10; Fig. 1), either directly or via a support housing (see Fig. 1, sections (Ref. 10) are directly connected to feet Ref. 12), wherein the feet (12) and the support housing (26) stands freely and is arranged in such a manner that open areas are formed around the support housing (26)(Fig. 1-2), and wherein at least some sections (see sections near Ref. 10) can be combined with each other and with the support housings (26) whereby the star configuration is changeable as desired (Page 2, Para. 0034, 0054); wherein the sections (see near Ref. 10) of the pipe frame are one of straight stainless steel pipes or round solid profiled parts (Fig. 1)(Page. 2. Para. 0039); wherein the sections (see near Ref. 10) of the profile frame are profiled parts whose bottoms are open (Page. 3, Para. 0051), and whole surfaces pointing away from the floor are one of curved or flat and slanted towards the floor (Page 2, Para. 0039); wherein each section (see near Ref. 10) presents at least one joining end (see connection points between Ref. 10, and Ref. 26, or Ref. 12)(Fig. 1), which fits with a connection interface of one of a support housing (26) or of a foot (12); wherein the individual sections in the pipe or profile frame have one of blunt impact or mitered impact joining ends (See Fig. 2); wherein the joining places in the pipe or profile frame have an external flat design and contain internal connection elements (17)(Fig. 1)(Page. 3, Para. 0052); wherein in or on the pipe or profile frame (10), covers (22) are provided at least in some areas (Fig. 1); wherein the section of the pipe frame (see sections near Ref. 10) have substantially identical external diameters (Fig. 1); wherein the covers (22)

Art Unit: 3651

are one of grids, metal plate parts, plastic parts, or glass parts ("metal sheets", Page. 2, Para. 0040).

Relative to claim 1 Stocchi does not expressly disclose the support structure (10) is one of a pipe or profile frame. However, Stocchi teaches the use of pipes in a container handling apparatus support structure of this type is well known in the art (Page. 1)(Para. 0007). Although it is apparent from the drawings that the sections (see near Ref. 10) are composed of pipe or profile frame, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the device of Stocchi with sections of pipe or profile frame since it is well known in the art of container handling apparatus.

Relative to claim 5, Stocchi does not expressly disclose: wherein in a top view with the viewing direction towards the floor, the thickness of the section (see sections near Ref. 10) is smaller than the diameter of the support housing (26) and of the feet (12). As suggested by the Stocchi, the device of Stocchi can be modified so that the thickness of the sections is smaller than the diameter of the support housing (26) and of the feet sections (12), since providing thin sections would leave useful space beneath the sections to accommodate additional components (Page 3, Para. 0054).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the device of Stocchi so that the sections are smaller in diameter than the support housing and the feet as mentioned above to provide useful space beneath the sections to accommodate additional components.

Art Unit: 3651

Claims 2-4, 11-14, 16-17, 19-21, and 23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Stocchi in view of Petri et al (US Patent No. 6,058,985).

Relative to claims 2-4, 11-14, 16-17, 19-21 and 23, Stocchi discloses all claim limitations, including: a splash removal device (40)(Page. 3, Para. 0058), and wherein the entry and exit stars(14) are arranged inside of the external circumference that is defined by externally located sections (see near Ref. 10) of the pipe or profile frame (Fig. 1-2).

Stocchi does not expressly disclose: at least one additional container handling component that is fixed at a node of one of the pipe or profile frame; at least one additional container handling component that is fixed on one of sections; wherein at least some of the entry and exit stars have individual drives accommodated in their support housings, and control and supply strands leading to the individual drive systems arranged in the sections of the pipe or profile frame; wherein, beneath the fixation plane of the pipe or profile frame, on the bottom sides of the support housings, drive wheels are arranged free-standing and connected via overhung drive devices with a central drive system; wherein the drive accommodated in the support housings can be driven by drive strands placed in sections; wherein each support housing has a narrow upper part and a broadened foot part, and is mounted with a foot part on a bottom housing, which forms the node of the pipe and profile frame, where on the bottom housing at least two section connecting interfaces are provided, which are offset about the axis; wherein the container handling component comprises a closing device, inspection device, or a labeling machine; wherein the container handling component comprises a

Art Unit: 3651

conveyor; wherein the individual driver are electrical servo motors with drive systems or electrical direct drive motors; wherein the drive wheels are one of sprocket wheels, toothed wheels or belt toothed wheels; wherein the narrow upper part tapers upwardly; or wherein each additional container component is also arranged inside of the external circumference.

Petri teaches: at least one additional container handling component (4)(Fig. 1)(108)(Fig. 4); that is fixed at a node of one of the pipe or profile frame (Fig. 1)(Col. 3, lines 23-44); at least one additional container handling component (4)(108) that is fixed on one of sections; wherein at least some of the entry and exit stars have individual drives (150, 160) accommodated in their support housings (Col. 2, lines 46-65), and control and supply strands leading to the individual drive systems arranged in the sections of the pipe or profile frame (Col. 3, lines 43-46); wherein, beneath the fixation plane of the pipe or profile frame, on the bottom sides of the support housings, drive wheels are arranged free-standing and connected via overhung drive devices with a central drive system (Col. 2, lines 58-62); wherein the drive (150, 160) accommodated in the support housings can be driven by drive strands placed in sections (Col. 2, lines 48-62); wherein each support housing (8) has a narrow upper part and a broadened foot part (Col. 2, lines 62-65), and is mounted with a foot part on a bottom housing (Fig. 1), which forms the node of the pipe and profile frame, where on the bottom housing at least two section connecting interfaces are provided, which are offset about the axis (Fig. 1-2); wherein the container handling component comprises a closing device (106). inspection device, or a labeling machine (108)(Col. 3, lines 22-35); wherein the

Art Unit: 3651

container handling component comprises a conveyor (CoI. 2, lines 39-45; CoI. 3, lines 22-30); wherein the individual driver are electrical servo motors with drive systems or electrical direct drive motors (CoI. 3, lines, 43-46); wherein the drive wheels are one of sprocket wheels, toothed wheels or belt toothed wheels (CoI. 2, lines 59-62); wherein the narrow upper part tapers upwardly (Ref. 8, CoI. 2, lines 63-65)(Fig. 1); or wherein each additional container component is also arranged inside of the external circumference (Fig. 1)(CoI. 3, lines 22-43).

Petri teaches the additional handling containers including a closing and labeling device, individual drives in the support housings, drive wheels, and drive strands as mentioned above for the purpose of providing a bottle handling apparatus with an improved setup structure that is hygienic, minimizes the collection of dirt, and is also easy to clean (Col. 1, lines 39-44).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the device of Stocchi, modified as above, with the additional handling drives, individual drives in the support housing, drive wheels, and drive strands mentioned above as taught in Petri for the purpose of providing a bottle handling apparatus with an improved setup structure that is hygienic, minimizes the collection of dirt, and is also easy to clean.

Application/Control Number: 10/588,327 Page 9

Art Unit: 3651

Additional Cited Art

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Relative to claims 2 and 19, see Fiegler, (US PG Pub. 2006/0207859; Para. 0014; 0029-0030).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to YOLANDA CUMBESS whose telephone number is (571)270-5527. The examiner can normally be reached on MON-THUR 9AM-6:00PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, GENE CRAWFORD can be reached on 571-272-6911. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

Application/Control Number: 10/588,327 Page 10

Art Unit: 3651

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Gene Crawford/ Supervisory Patent Examiner, Art Unit 3651

/YOLANDA CUMBESS/ Examiner, Art Unit 3651